

ROMAN SHADES RANGE

Bandalux roman shades are available in a variety of styles and options thanks to the different manufacturing possibilities and the wide variety of MOVES collection fabrics. A perfect shade to match with traditional decorating styles.



AVAILABLE COMPONENT COLORS



White
RAL 9016



Aluminum

● CIES XXL only available in white.

OPERATING SYSTEMS



Chain



Cord



Motor

MAX. WIDTH

4000 mm

MAX. HEIGHT

4000 mm

ROMAN SHADES RANGE

PRODUCT PRESENTATION

Systems and manufacturing

	Mini Skorpio	Skorpio	Toxa	Cies XXL
				
Maximum width ⁽¹⁾ (WxH)	1600 x 1870 mm	3000 x 2000 mm	4000 x 3200 mm	4000 x 4000 mm
Maximum height ⁽¹⁾ (WxH)	1000 x 3000 mm	2000 x 3000 mm	3760 x 3400 mm	4000 x 4000 mm
Colors	White RAL 9010 Aluminum	White RAL 9010 Aluminum	White RAL 9010 Aluminum	White RAL 9010
Chain	✗	✗	✓	✓
Cord	✓	✓	✗	✗
Motor	✗	✗	✓	✓
Manufacturing	Classic, Bar, Soft and Pacchetto			
Options	Double drop Double fabric	Double drop Double fabric Sloped track	Double drop Double fabric Safekids	Double drop Double fabric Safekids

① (1) Approximate maximum measurements. They may vary depending on the fabric and system.

New motorized option with external solar panel



NEW

The Bandalux Solar Station Kit offers a motorized, sustainable and self-sufficient roman shade solution powered by sunlight; no electrical installation required.

The kit includes a solar panel, a rechargeable battery and a motor, making it an eco-friendly and efficient choice that eliminates the need for electrical wiring.

To maximize sunlight capture, the solar panel and battery should be installed outdoors (e.g., on a façade or roof). The motor is built into the blind's tube or rod and connected to the solar panel with wiring.*

*Includes a 50 cm cable. Compatible with an optional 3 m extension cable.

ROMAN SHADES RANGE

PRODUCT PRESENTATION

Different manufacturing options

Three different options WITH RIBBING to make the shade more rigid.




An option WITHOUT RIBBING for free-falling fabric.



Chain, motor or cord operated

Chain and motor



TOXA

Compact track for shades up to 3400 mm high or 4000 mm in width.

Chain: max. surface 8,4 m²
Motor: max. surface 12,8 m²




CÍES XXL

Track for large sizes shades up to 4000 mm high and 4000 mm in width.

Chain: max. surface 16 m²
Motor: max. surface 16 m²


Cord



SKORPIO

Track for shades up to 3000 mm high or 3000 mm in width.

Max. surface 6 m²



MINI SKORPIO

Track for shades up to 3000 mm high or 1600 mm in width.

Max. surface 3 m²

Components matched to the fabric


All the roman shades components - yarns, tape, cord, rods, counterweights - are color-coordinated with the fabric for a great aesthetic visual effect.

SLIDING PANEL RANGE

PRODUCT PRESENTATION

Safety first

Bandalux prioritizes security and therefore supplies by default a child safety system that holds the cord or chain tight to the wall to prevent children from getting entangled in it.



SafeKids

Patented by Bandalux.

Highly efficient security device that ensures the attachment of the cord or the chain to the wall. The shade can only be operated if the device is installed.



Child Safety

Standard security device in the market that is served by default.

Children can get tangled up with the shade/blind cord or chain

Always keep the chain or cord of the shades out of the reach of children. Since children can climb furniture, make sure to put the cribs, playpens or any furniture away from cords or chains.


The supplied safety device (see photo) must always be securely attached to the wall and hold tightly the cord or chain, thus preventing children from pulling them around the neck.

By default, Bandalux will always provide all shades and blinds with Child Safety System. When not necessary due to the absence of children, the waiver must be signed.

Bandalux will not be responsible for installation by third parties. It is the responsibility of the installer to correctly place the child safety system.

LYNX, smart blinds

Coming soon



Available for
Android and iOS.
Compatible with:



▼ Contactless comfort

Manage your blinds from your Smartphone or via voice control.

▼ Atmospheres personalization

Program and automate as many scenes as you want and confirm the position of your blinds at any time.

▼ Peace of mind

Enable presence simulation scenes when you are away from home.

▼ Efficiency and savings

Take advantage of sunlight cycles, react to the climatic conditions and, as a consequence, save on your electricity bill.

▼ Connected environment

In addition to blinds, LYNX allows you to connect other elements such as music, lamps, fans...

ROMAN SHADES RANGE

OPTIONS

Manufacture

WITH RODS

Classic



Served by default

Bar



Soft



WITHOUT RODS

Pacchetto



Colors

Profiles

- White RAL 9010
- Aluminum

Chain

- White
- Ivory
- Grey
- Black
- Brown
- Transparent

SafeKids

- Black
- Brown
- White
- Ivory
- Grey

By default, Bandalux will provide the track in white. If you prefer a different color, please indicate it on the order form. / Cies XXL system only available in white. / The colors of the thread, tape, cord, wands and the counterweight will be coordinated with the color of the chosen fabric.

Operating system and child safety systems

CHAIN

Toxa system



Served by default

Cies XXL system



Child Safety



Served by default

SafeKids



CORD

Skorpio system



Mini Skorpio system



Child Safety



ROMAN SHADES RANGE

OPTIONS

Motors

Toxa system



Cies XXL system



MOTOR ⁽³⁾		AUTOMATISMS ⁽⁴⁾		
		Single-Channel remote	Multi-Channel remote	Other
Toxa system	Hardwired 24Vdc	Somfy®	LW25 0.8/30 Transformer required	Transformer 24Vdc + Pulsador Inis DC ⁽¹⁾ Ref. 02463101
	Radio 24Vdc	Somfy®	LW25 0.8/30 Transformer required	Transformer 1.5 DC ⁽¹⁾ Ref. 02462040
				Inverter 24Vdc Ref. 02464010
Cies XXL System	Hardwired 230V	Bandalux	VERONA 40 3/30	Transformer 1.5 DC ⁽¹⁾ Ref. 02462040
		Somfy®	MERCURE 40 3/30	
		Somfy® Silent	SONESSE 40 3/30	
	Radio 230Vac	Bandalux Radio	BANDALUX 40 3/30	Elegance 1 White Ref. 06702000A
Cies XXL System	Radio 230Vac	Somfy® RTS	ALTUS 40 3/30	Elegance 4 White Ref. 06702100B
		Somfy® RTS Quiet	SONESSE 40 3/30	Situo 1 RTS Pure Ref. 06700970D
		Somfy® IO	SUNEA SCREEN 40 3/30	Situo 5 RTS Pure Ref. 06700881D
Radio IO 230Vac	Radio IO 230Vac	Somfy® IO Quiet	SONESSE 40 3/30	Situo 1 IO Pure Ref. 06700620B
		Bandalux external panel	KIT SOLAR STATION 40 10/12	Situo 5 IO Pure Ref. 06700625B
	Radio Solar 12Vdc		Transmitter 1 Channel Ref. 06700073	Transmitter 5 Channel Ref. 06700074

⁽¹⁾ (1) The price of the transformer must be added to the price of the motorization. / (2) It is necessary to add a receiver to the price of the motorization. The integrated receiver can be installed in the blinds with a width greater than 760mm. / (3) Check fabric-based manufacturing limits according to motor type on page 9.

ROMAN SHADES RANGE

OPTIONS

Assembled systems

Assembled Toxa system

⚠ Minimum order 1 m.


Assembled Cíes XXL system

⚠ Minimum order 1 m.


Assembled Skorpio system

⚠ Minimum order 1 m.

Supports and reinforcements



Short reinforced
bracket with
extension



Long reinforced
bracket with
extension



Universal support
for window
(no perforating
necessary)

Other options



Double drop

⚠ Bandalux recommends using
two independent shades.



Sloped track

⚠ Skorpio system only.



Waves and squares

⚠ Minimum order 1 m.



Changing distance
between pleats

Double fabric and blackout lining

⚠ Only available for Classic confection. / Dimensional limits may
be affected. Please consult your sales representative / For more
information, see page 9.

Rings on all tapes

Additional charge for roller

ROMAN SHADES RANGE

TECHNICAL DATA

Minimum and maximum sizes

Model	Operating system	Shade width		Shade height		Surface	
		Minimum	Maximum	Minimum	Maximum	Minimum	Maximum
MINI SKORPIO	CORD	300 mm	1600 mm	300 mm	3000 mm	0,09 m ²	3 m ²
SKORPIO	CORD	400 mm	3000 mm	500 mm	3000 mm	0,20 m ²	6 m ²
TOXA	CHAIN	400 mm	4000 mm	500 mm	3400 mm	0,20 m ²	8,4 m ²
	MOTOR	800 mm	4000 mm	500 mm	3400 mm	0,40 m ²	12,8 m ² ⁽²⁾
CÍES XXL	CHAIN	560 mm	4000 mm	500 mm	4000 mm	0,20 m ²	16 m ²
	MOTOR	560 mm ⁽¹⁾	4000 mm	500 mm	4000 mm	0,30 m ²	16 m ²

⁽¹⁾ (1)Check available motors and minimum shade width on pag. 8. / ⁽²⁾ For the motor-operated Toxa system with Polyscreen® fabric, the maximum surface size is 8,5 m².


Number of brackets according to shade width

Shade width (mm)	Nº brackets
Up to 1240	2
1250 -1990	3
2000 -2990	4
3000 -3990	5
4000	6

Number of cords according to shade width

CLASSIC/BAR/SOFT		PACCHETTO	
Shade width (mm)	Cords	Shade width (mm)	Cords
Up to 1240	2	Up to 1000	2
1250 -2000	3	1010-1410	3
2010 -2500	4	1420 -2000	4
2510-3000	5	2010 -2500	5
From 3000	6	251-3000	6

Manufacturing tolerance



⁽¹⁾ In accordance with the european standard EN13120.


Stacking heights

Model	Mini Skorpio	Skorpio	Toxa	Cíes XXL
CLASSIC	370 mm	370 mm	300 mm	370 mm
BAR	370 mm	370 mm	300 mm	370 mm
SOFT	340 mm	340 mm	270 mm	270 mm
PACCHETTO	300 mm	250 mm	230 mm	300 mm


⁽¹⁾ The approximate stacking height has been calculated based on a shade measuring 3000mm.

Cross-sectional drawing and heights of each system


MINI SKORPIO




SKORPIO



TOXA



CÍES XXL




ROMAN SHADES RANGE

TECHNICAL DATA

Controls height

CHAIN OR CORD OPERATING SYSTEM WITH CHILD SAFETY SYSTEM

The Child Safety piece must be positioned at a minimum height of 1500mm from the floor.
To calculate the controls height (hc) see the following diagram:




CHAIN OR CORD OPERATING SYSTEM WITHOUT CHILD SAFETY SYSTEM

If Child Safety/Safekids is waived, the control height will be:

Shade height (H)	Controls height (hc)
≤2200 mm	Shade height - 100 mm
+2210 mm	Shade height - 1000 mm

The result will be rounded to the next size down on the chart below (hc available):



If you would like to position the controls at a specific height (hc), please indicate the desired height on the order form, using the chart below (available hc).

If you do not specify the controls height and you have signed the Child Safety waiver, Bandalux will manufacture the Skorpio system with the control cord sewn into the bottom of the shade, using a ring.

Available hc:
820 mm
1070 mm
1320 mm
1570 mm
1820 mm
2070 mm
2320 mm
2570 mm
2820 mm
3070 mm

ROMAN SHADES RANGE

TECHNICAL DATA

Available motors and minimum shade width

	Type	System	Motor name	Voltage (V)	Ø mm	Nm	r.p.m	Power (W)	Intensity (A)	Min. width shade (mm)
BANDALUX	HARDWIRED 	CÍES XXL	VERONA 40 3/30	230	40	3	30	90	0,39	650
	RADIO	CÍES XXL	BANDALUX 40 3/30	230	40	3	30	90	0,39	650
	RADIO SOLAR 	CÍES XXL	KIT SOLAR STATION 40 10/12	12	40	10	12	36	3	740
SOMFY®	HARDWIRED 	TOXA	LW25 0,8/30	24	25	0,8	30	28,8	1,20	800
		CÍES XXL	MERCURE 40 3/30	230	40	3	30	80	0,35	620
	HARDWIRED QUIET 	CÍES XXL	SONESSE 40 3/30	230	40	3	30	95	0,41	610
SOMFY®	RTS	CÍES XXL	ALTUS 40 3/30	230	40	3	30	80	0,35	630
	RTS QUIET	CÍES XXL	SONESSE 40 3/30	230	40	3	30	95	0,41	740
	IO	CÍES XXL	SUNEA SCREEN 40 3/30	230	40	3	30	90	0,39	630
SOMFY®	IO QUIET	CÍES XXL	SONESSE 40 3/30	230	40	3	30	95	0,41	740

Double fabric

(Only available for Classic confection)

Lining or double fabric allows you to combine two collections of different fabrics in one blind, in order to unify the exterior aspect of the façade or combine 2 fabrics.

Bandalux recommends this option for fabrics with the same composition and cleaning indications to avoid shrinkage incident.

Double blackout fabric

(Only available for Classic confection)

To darken a room without losing the decorative characteristics of the fabric, Bandalux gives you the choice of a lining in Blackout fabric.



BANDALUX