

PREMIUM PLUS

Premium Plus shades have a very versatile and multi-purpose design that suits any need thanks to its diverse guiding options, its operating systems and its installing options. Its minimized design includes an extraslim cover that reduces the gap between brackets and is also visually delicate. Available in two different sizes depending on the shade measurements. A double shade that combines decorative with technical fabrics can be configured.



AVAILABLE COMPONENT COLORS



White
RAL 9016



Black
RAL 9011



Brown
RAL 8019



Grey
RAL 9006



Ivory
RAL 1013

OPERATING SYSTEMS



Chain



Crank



Motor

MAXIMUM WIDTH

4600 x 4600 mm

MAXIMUM HEIGHT

4600 x **4600 mm** (indoor instal.)

4600 x **3000 mm** (cable guide outdoor instal.)


4600 x **4000 MM** (aluminum channel outdoor instal.)

● Check 'Fabric Limits' in ProArea.

PREMIUM PLUS

New prop side system

Bandalux has developed stronger idle ends to deliver benchmark endurance and reliability. It can be easily set up by a simple one hand move thanks to its internal compression spring.




Double drop (transmission)

Bandalux's new transmission delivers enhanced smoothness enabling two rolling tubes to operate with just one operating system. It also allows aligning both drops. It contains a solid system with high quality bearings that provides a perfect, smooth and silent (motion) rotation.



Minimum space between fabric and bracket

This light system design has been renewed to minimize the space between fabrics and, this way, reducing the GAP and the possible incoming light.



Optional pelmets and decorative covers

Premium Plus shades can be set with optional pelmets and decorative covers as a distinguishing element to enhance the system aesthetics. The Trazer pelmet and the Q-Box and Q-Style covers will highlight the shade's finishing and also personalizing its design or using one of the designs offered by Bandalux.

Trazer



Trazer Corner piece



Q-Box



Q-Style



Junction profile for an easier installation

The junction profile compact design makes the system adjust to any kind of surface, facilitating its installation. Only available for Premium Plus I.



Two sizes

Different measures related to each shade size. A reduced size design and a totally flat cover provide a very light visual effect for the shade even in its larger size.

A : Premium Plus I
B : Premium Plus II



PREMIUM PLUS

Improved chain operating: rugged, smooth and durable

Smooth and silent drive, thanks to the use of materials that allow a high precision geometry.



The springs, of German technology and manufacture, calibrated and heat-treated, provide greater resistance to the system.

All elements susceptible to wear and tear are made of steel, thus ensuring the durability of the entire mechanism.

Maximum comfort and softness of use

Redux mechanism

The REDUX mechanism has an internal planetary gear system that reduces drive effort by up to 30%.


The planetary system requires a chain displacement higher than the height of the shade, so this system does not have mechanical stops to fix the end of the stroke at the top and at the bottom.

Note: Since the system has no limit switch, users need to be careful when operating the blind to keep the fabric from unrolling/rolling up too far.



Redux mechanism I

Redux mechanism II



Planetary

Assisted spring

Ideal to reduce the feeling of weight on shades larger than 5m² (with limit switch).

Example :

Effort when manoeuvring a 3,6 x 4m shade :

without spring : 4'8kg
with spring : 2'2kg
(with limit switch)



Child safety

Bandalux prioritizes security and therefore supplies by default a child safety system that holds the chain tight to the wall to prevent children from getting entangled in it.

Child Safety

Standard security device in the market that is served by default.

Safekids, patented by Bandalux

Highly efficient security device that ensures the attachment of the chain to the wall. The shade can only be operated if the device is installed.

Child Safety



Safekids



Smooth and silent motorization

All Bandalux motorization products include a brand new, hybrid technology driving wheel specifically designed by us to minimize noise and vibration.



BANDALUX



230Vac



Rechargeable battery

SOMFY®



230Vac

New motorized option with external solar panel



The Bandalux Solar Station Kit offers a motorized, sustainable and self-sufficient Premium Plus solution powered by sunlight; no electrical installation required.

The kit includes a solar panel, a rechargeable battery and a motor, making it an eco-friendly and efficient choice that eliminates the need for electrical wiring.

To maximize sunlight capture, the solar panel and battery should be installed outdoors (e.g., on a façade or roof). The motor is built into the blind's tube or rod and connected to the solar panel with wiring.⁽¹⁾

(1) (1) Includes a 500 mm cable. Compatible with an optional 3 m extension cable.

PREMIUM PLUS

LYNX, smart blinds

The app that allows you to control all Bandalux window coverings solutions, wherever you are.



Available for
Android and iOS.
Compatible with:



amazon alexa



Google Home

Contactless comfort

Manage your blinds from your Smartphone or via voice control.

Atmospheres personalization

Program and automate as many scenes as you want and confirm the position of your blinds at any time.

Peace of mind

Enable presence simulation scenes when you are away from home.

Efficiency and savings

Take advantage of sunlight cycles, react to the climatic conditions and, as a consequence, save on your electricity bill.

Connected environment

In addition to blinds, LYNX allows you to connect other elements such as music, lamps, fans...


Customizable system

Color variety

Premium Plus shades offer a large range of colors (5 different) to personalize the operating system and its parts such as covers, brackets or chains.



White
RAL 9016



Black
RAL 9011



Brown
RAL 8019



Grey
RAL 9006



Ivory
RAL 1013

Different bottom bar options

The bottom bar becomes a distinguishing feature for the shade's finishing :

Slim 25



Slim 35



Teardrop



Hidden

(ø 20 mm, ø 30 mm)




Mini Plain



Exclusively for
telescopic guide.

Double shade

Two shades on a single bracket that enables you to combine an opaque and a decorative fabric.



Optimal fabric fastening

This system offers multiple side guide options for either indoor or outdoor installations. Cable guides and aluminum side channels that improve raising or lowering the fabric efficiently as well contributing to minimize the GAP between the side guide and the fabric –one of Bandalux main priorities. The system is set with different types of side guides specifically developed depending on the operating system :

Cable guides, U-201 and U-301

Hold the fabric well and allow outdoor installation.



R2 channel

Ideal for semi-hidden systems. The external channel adapts to wall irregularities while the internal channel adapts to the fabric drop.




Air purifying shades

As a result of Bandalux' ongoing technological innovation and its commitment to sustainability, it has launched a new shade able to purify the air in any room.


Application of a nanocoating on the technical fabric

The shade is treated as follows:



A mixture of oxide minerals is applied to the shade's fabric.

This mixture is naturally activated by sunlight or artificial lighting.



When it is activated, any contaminant particles in the air are removed (viruses, bacteria, fungi, contamination, and volatile organic compounds).


Great versatility

- Applicable to all Roller Shades systems, Box range, Fit Box, Skylight and Sliding Panel.
- Available in the Polyscreen® 550 and Mega BO fabrics, in a range of colors.

POLYSCREEN® 550 AIRPURE®



MEGA BO AIRPURE®



PREMIUM PLUS

OPTIONS

Standard configuration

Colors



! The components color will be paired with the chosen fabric according to Bandalux criteria.

Chain operated



Ø 20 mm hidden bottom bar⁽¹⁾



Child Safety chain retainer



! Optional : Safekids device.

! (1) Fabrics incompatible with hidden bottom bar will be served with Slim 25 bottom bar by default.

Optional configuration

Long brackets



Transparent chain



Teardrop hidden bottom bar⁽¹⁾



Ø 30 mm hidden bottom bar



Slim 25 bottom bar⁽¹⁾



Slim 35 bottom bar



Mini Plain bottom bar (exclusive 'R2' channel)



! Only for Premium Plus I.

! (1) Maximum width : 2500 mm.



Operating systems

CRANK


(only available for Premium Plus II)



Fixed



Removable



with crank return

Max 300 mm

MOTOR (includes limit switch programming)

MOTOR ⁽¹⁾			AUTOMATISMS ⁽²⁾			
			SINGLE-CHANNEL REMOTE	MULTI-CHANNEL REMOTE	OTHER	
Hardwired 230Vac	PPI	Bandalux	VERONA 40 3/30	--	Somfy® Smoove Uno Ref. 06700610B	
	PPI	Somfy®	MERCURE 40 3/30			
	PPI		ARIES 40 SHORT 4/16			
	PPI	Somfy® Quiet ⁽³⁾	SONESSE 40 3/30			
	PPI	Bandalux	M2 50 6/32, 20/17			
	PPI		ARIANE 50 6/32			
Radio 230Vac	PPI	Somfy®	ATLAS 50 15/32	--		
	PPI		MAESTRIA 50 WT 6/17, 10/17, 15/17 ⁽⁴⁾			
	PPI	Somfy® Quiet ⁽³⁾	SONESSE 50 6/28, 10/28, 15/17			
	PPI	Bandalux Radio	R2 40 3/30	Elegance 1 White Ref. 06702000A	Elegance 4 White Ref. 06702100B	
	PPI	Somfy® RTS	ALTUS 40 3/30	Situo 1 RTS Pure Ref. 06700970D	Situo 5 RTS Pure Ref. 06700881D	
	PPI	Somfy® RTS Quiet ⁽³⁾	SONESSE 40 3/30			
Radio IO 230Vac	PPI	Bandalux Radio	R2 50 6/32, 20/17	Elegance 1 White Ref. 06702000A	Elegance 4 White Ref. 06702100A	
	PPI	Somfy® RTS	ALTUS 50 6/32, 15/17	Situo 1 RTS Pure Ref. 06700970D	Situo 5 RTS Pure Ref. 06700881D	
	PPI	Somfy® RTS Quiet ⁽³⁾	SONESSE 50 6/28, 10/28, 15/17			
	PPI	Somfy® IO	SUNEA SCREEN 40 3/30	Situo 1 IO Pure Ref. 06700620B	Situo 5 IO Pure Ref. 06700625B	
	PPI	Somfy® IO Quiet ⁽³⁾	SUNEA SCREEN 50 6/32, 15/32			
	PPI	Bandalux Radio ⁽³⁾	RECHARGEABLE BI 35 6/24	1 CH Transmitter White Ref. 06701100B	15 CH Transmitter White Ref. 06701110B	
Battery 12Vdc	PPI	Bandalux Radio Quiet ⁽³⁾	RECHARGEABLE BI 50 11/13		Charger AC Rechargeable battery Ref. 06701215 + USB Wire Type C Ref. 06701275	
	PPI	Bandalux external panel	KIT SOLAR STATION 40 10/12	1 CH transmitter Ref. 06700073	5 CH transmitter Ref. 06700074	
	PPI		KIT SOLAR STATION 50 20/16		--	

! (1) See motor characteristics on page 71. / (2) See other colors and automatisms on Motorization section page 92. / (3) Motor only compatible for indoor installation. / (4) Motor with electronic limit switch. / For safety reasons, it is recommended to associate a wind sensor to ourdoor installation shades. For sizes bigger than 9m², associating this sensor will be essential.

Reduced effort for chain-operated systems



Redux I mechanism
(for Premium Plus I)



Redux II mechanism
(for Premium Plus II)



Assisted spring

Bandalux recommends REDUX MECHANISM :

Mechanism that **eases the drive and reduces the feeling of weight by 30 %.**

! Redux mechanism does not include a limit switch. / The chain loop length is three times the shade length.

Recommended from 5m²

Example for a 3,6 x 4m shade :


- Without assisted spring = 4,8 kg.
- With assisted spring = 2,2 kg.
(with limit switch)

Side guides

ALUMINUM



'U - 201' Low lateral



'U - 301' Compact frontal
'U - 301' Compact lateral



'R2' Telescopic frontal
'R2' Telescopic lateral



Sill bottom for R2 Telescopic channel

!

Only compatible with Mini Plain bottom bar. / Maximum height 3500 mm.

CABLE

Wall fastening



Floor fastening



INDOOR/OUTDOOR
stainless ø 3,5 mm

Ceiling/Floor

Ceiling/Wall

Wall/Floor

Wall/Wall

TS

TP

PS

PP

!

Compatible with bottom bars : ø 20, ø 30 mm hidden and Slim 25/35.

Junction profile (only for Premium Plus I)



Simple installation

Colors



! During the installation, the fastening bracket must be placed as close as possible to the edge on the controls side. / Install a bracket every 500 mm. / Only for chain and motor-operated systems. / Incompatible with side guides.

Collection Airpure®

Airpure® Shades:



• Collection Polyscreen® 550 Airpure® in the following colors: Ash, Pearl, White, White Linen and White Pearl.

• Collection Mega BO Airpure® in the following colors: Alabaster, Black, Dark Grey and White.

PREMIUM PLUS

OPTIONS

Trazer pelmet


For more information please check 'A4 Decorative covers' Price List.

Trazer 100



Prices do not include projection section. / Minimum invoice 1 m. / Motor-operated system only compatible with Premium Plus II motors. / Mount plate included in standard sizes.

Projection



Check technical data on page 75.

Configurable Mount plate



Mount plate size only configurable for ceiling installations. / Check maximum and minimum measurements on page 75.

Corner piece 100



Incompatible with existing shades.

Q-Box



To add a decorative cover with your roller shade please check 'A3 Roller shades with decorative cassette' Price List.

Q-Box 85 Q-Box 100

Q-Style



To add a decorative cover with your roller shade please check 'A3 Roller shades with decorative cassette' Price List.

Q-Style 85 Q-Style 100

Other options



Double shade with 2 operating systems


Not available for crank-operated systems.



Digital Printing



Safekids (child safety system)



Double drop with 2 operating systems (double support)



Double drop with 1 operating system (transmission)

The sum of the double drop shall not exceed 4,6 m. Each drop may not exceed the maximum shade size indicated according to the fabrication limits. See the book 'Fabric limits - Fabrics Collection' in AreaPro. For the non-driven drop, the fabrication limits for chain-driven (no motor, no crank) will be taken into account.



No ending chain ring

For measurements from 304 cm, only available in white and black color.



Metallic chain

Chain tensioner not included.

PREMIUM PLUS

TECHNICAL DATA

Operating systems and minimum shade width

OPERATING SYSTEM	MOTOR NAME	Voltage (V)	Ø (mm)	Nm	r.p.m.	Power (W)	Current (A)	Min. shade width (mm)
CHAIN	--	--	--	--	--	--	--	200 ⁽¹⁾
CRANK	--	--	--	--	--	--	--	400
BANDALUX HARDWIRED	VERONA 40 3/30	230	40	3	30	90	0,39	610
	MODENA 50 6/32	230	50	6	32	120	0,52	660
	BARI 50 20/17	230	50	20	17	160	0,7	710
BANDALUX RADIO	R2 40 3/30	230	40	3	30	90	0,39	610
	R2 50 6/32	230	50	6	32	120	0,52	710
	R2 50 20/17	230	50	20	17	160	0,7	730
BANDALUX RADIO BATTERY ⁽²⁾	BI 35 6/24	12	35	6	24	38	3,23	830
BANDALUX RADIO BATTERY QUIET ⁽²⁾	BI 50 13/11	12	50	13	11	40	3,50	970
BANDALUX RADIO SOLAR	KIT SOLAR STATION 40 10/12	12	40	10	12	36	3	630
	KIT SOLAR STATION 50 20/16	12	50	20	16	72	6	680
SOMFY® HARDWIRED	MERCURE 40 3/30	230	40	3	30	80	0,35	610
	ARIES 40 SHORT 4/16	230	40	4	16	65	0,28	540
	ARIANE 50 6/32	230	50	6	32	120	0,52	660
	ATLAS 50 15/32	230	50	15	32	240	1,04	740
	MAESTRIA 50 WT 6/17 ⁽³⁾	230	50	6	17	90	0,45	690
	MAESTRIA 50 WT 10/17 ⁽³⁾	230	50	10	17	120	0,50	690
	MAESTRIA 50 WT 15/17 ⁽³⁾	230	50	15	17	140	0,65	740
SOMFY® HARDWIRED QUIET ⁽²⁾	SONESSE 40 3/30	230	40	3	30	95	0,41	610
	SONESSE 50 6/28	230	50	6	28	146	0,63	750
	SONESSE 50 10/28	230	50	10	28	180	0,78	750
	SONESSE 50 15/17	230	50	15	17	153	0,67	750
SOMFY® RTS	ALTUS 40 3/30	230	40	3	30	80	0,35	640
	ALTUS 50 6/32	230	50	6	32	90	0,39	790
	ALTUS 50 15/17	230	50	15	17	140	0,61	790
SOMFY® RTS QUIET ⁽²⁾	SONESSE 40 3/30	230	40	3	30	95	0,41	650
	SONESSE 50 6/28	230	50	6	28	146	0,63	930
	SONESSE 50 10/28	230	50	10	28	180	0,78	930
	SONESSE 50 15/17	230	50	15	17	153	0,67	930
SOMFY® IO	SUNEA SCREEN 40 3/30	230	40	3	30	90	0,39	640
	SUNEA SCREEN 50 6/32	230	50	6	32	120	0,52	790
	SUNEA SCREEN 50 15/32	230	50	15	32	240	1,04	810
SOMFY® IO QUIET ⁽²⁾	SONESSE 40 IO 3/30	230	40	3	30	95	0,91	690


(1) For widths between 200 mm and 400 mm, maximum height without side guides will be 1500 mm. Guiding needed for larger heights. / **(2)** Motor only compatible for indoor installation. / **(3)** Motor with electronic limit switch. / To guarantee proper functioning, Bandalux will provide the right motor model for the shade size.




PREMIUM PLUS

TECHNICAL DATA


Space between bracket and fabric (GAP)



One shade with 1 op. system



Two shades with 1 op. system



Two shades with 2 op. systems

w1 Support side

w2 Controls side

		without side guides				with cable guides			
		w1	w2	w3	w4	w1	w2	w3	w4
PREMIUM PLUS I	CHAIN	21 mm	20 mm	32 mm	33 mm	21 mm	20 mm	-	-
	MOTOR	21 mm	23 mm	32 mm	33 mm	21 mm	23 mm	-	-
PREMIUM PLUS II	CHAIN	21 mm	20 mm	32 mm	33 mm	21 mm	20 mm	-	-
	CRANK	21 mm	32 mm	32 mm	33 mm	21 mm	32 mm	-	-
	MOTOR ⁽¹⁾	21 mm	25 mm	32 mm	33 mm	21 mm	25 mm	-	-

! (1) Add 3 mm on the controls side for Bandalux ø 50 mm motor-operated systems.

Controls height

CHAIN

CHAIN-OPERATED WITH CHILD SAFETY SYSTEM

The **Child Safety/Safekids** device must be positioned at minimum 1,5 m from the floor. To calculate the controls height (hc), **see page 107**.

CHAIN-OPERATED WITHOUT CHILD SAFETY SYSTEM

If the Child Safety/Safekids feature is declined, the controls height will be :




Premium Plus I

Minimum calculation for hc :
 $H \times 0,70 + 50 \text{ mm}$

Premium Plus II

Minimum calculation for hc :
 $H \times 0,90 + 50 \text{ mm}$

CRANK



Recommended crank heights hc

1000 mm

1200 mm

1400 mm

1600 mm

1800 mm

2000 mm

2200 mm

2400 mm

2600 mm

2800 mm

3000 mm

Example of calculation

Shade height H	Controls height hc (minimum)	
	P. Plus I	P. Plus II
1000 mm	750 mm	950 mm
2000 mm	1450 mm	1850 mm
2500 mm	1800 mm	2300 mm
4000 mm	2850 mm	3650 mm

! 1. The controls height will always be measured from the top part of the shade (top of the bracket) to the bottom of the chain tensioner.



2. In single crank control, the controls height is considered with the crank in the operative position. Add 140 mm to obtain the crank extended measurement.

PREMIUM PLUS

TECHNICAL DATA



Side guides sizes

ALUMINUM CHANNEL




CABLE GUIDE


INDOOR/OUTDOOR stainless ø 3,5 mm



Bottom bars and retraction heights (mm)



Production tolerance





⚠ According to EN13120 European standard.

HIDDEN BOTTOM BARS



VISIBLE BOTTOM BARS



⚠ Only for R2 channel

ø 20 mm

ø 30 mm

Teardrop

Mini Plain

Slim 25

Slim35

	Ceiling	Wall		Ceiling	Wall		Ceiling	Wall		Ceiling	Wall		Ceiling	Wall				
		Min	Max															
PREMIUM PLUS I short bracket	h=100	w ₁ =1 w ₂ =62	w ₁ =18 w ₂ =80	h=110	w ₁ =1 w ₂ =57	w ₁ =13 w ₂ =75	h=100	w ₁ =5 w ₂ =67	w ₁ =23 w ₂ =85	h=117	w ₁ =6 w ₂ =68	w ₁ =24 w ₂ =86	h=105	w ₁ =5 w ₂ =67	w ₁ =23 w ₂ =85	h=115	w ₁ =1 w ₂ =63	w ₁ =29 w ₂ =81
PREMIUM PLUS I long bracket	h=128	w ₁ =28 w ₂ =90	w ₁ =46 w ₂ =108	h=138	w ₁ =23 w ₂ =85	w ₁ =41 w ₂ =103	h=128	w ₁ =33 w ₂ =95	w ₁ =51 w ₂ =113	h=145	w ₁ =34 w ₂ =96	w ₁ =52 w ₂ =114	h=133	w ₁ =33 w ₂ =95	w ₁ =51 w ₂ =113	h=143	w ₁ =29 w ₂ =91	w ₁ =47 w ₂ =109
PREMIUM PLUS II	h=120	w ₁ =2 w ₂ =77	w ₁ =22 w ₂ =100	h=130	w ₁ =2 w ₂ =72	w ₁ =17 w ₂ =95	h=120	w ₁ =5 w ₂ =82	w ₁ =27 w ₂ =105	h=138	w ₁ =6 w ₂ =83	w ₁ =28 w ₂ =106	h=125	w ₁ =5 w ₂ =82	w ₁ =27 w ₂ =105	h=135	w ₁ =2 w ₂ =78	w ₁ =23 w ₂ =101


PREMIUM PLUS

TECHNICAL DATA

Bracket sizes with cover and mechanisms


PREMIUM PLUS I

CHAIN : Short bracket





⚠ (l) Cable guiding : add 18 mm to bracket width.

CHAIN : Long bracket




PREMIUM PLUS II

CHAIN




⚠ (l) Cable guiding : add 18 mm to bracket width(l)


CRANK




MOTOR : Short bracket




MOTOR : Long bracket




MOTOR



DOUBLE SHADE



DOUBLE SHADE




PREMIUM PLUS

TECHNICAL DATA

Trazer technical information

CORNER PIECE SIZE




PROJECTION CUSTOMIZATION

(not available for the corner piece)

Projection width	
RECOMMENDED	125 mm
WITHOUT PROJECTION	0 mm
MINIMUM	50 mm
MAXIMUM	150 mm

SPACE BETWEEN BRACKET AND FABRIC



		w1	w2
100 mm TRAZER	CHAIN	29 mm	28 mm
	230Vac MOTOR	29 mm	33 mm
100 mm CORNER PIECE	CHAIN	29 mm	28 mm
	230Vac MOTOR	29 mm	33 mm

MOUNT PLATE CUSTOMIZATION

(not available for the corner piece)

Mount plate width	
STANDARD	125 mm
WITHOUT MOUNT PLATE	--
MINIMUM	125 mm
MAXIMUM ⁽¹⁾	190 mm

⁽¹⁾ (1) The mount plate can only be extended in a wall-mounted installation...

COMPATIBLE MOTORS

MOTOR TYPE	MOTOR NAME	Voltage (V)	Ø (mm)	Nm	r.p.m.	Power (W)	Current (A)	Min shade width (mm)
BANDALUX HARWIRED	M2 50 6/32	230	50	6	32	120	0,52	660
	M2 50 20/17	230	50	20	17	160	0,7	710
BANDALUX RADIO	R2 50 6/32	230	50	6	32	120	0,52	710
	R2 50 20/17	230	50	20	17	160	0,7	730
BANDALUX BATTERY QUIET ⁽¹⁾	RECHARGEABLE BI 50 13/11	12	50	13	11	40	3,50	970
SOMFY® HARWIRED	ARIANE 50 6/32	230	50	6	32	120	0,52	660
	ATLAS 50 15/32	230	50	15	32	240	1,04	740
	MAESTRIA 50 WT 6/17 ⁽²⁾	230	50	6	17	90	0,45	690
	MAESTRIA 50 WT 10/17 ⁽²⁾	230	50	10	17	120	0,50	690
	MAESTRIA 50 WT 15/17 ⁽²⁾	230	50	15	17	140	0,65	740
SOMFY® HARWIRED QUIET ⁽¹⁾	SONESSE 50 6/28	230	50	6	28	146	0,63	750
	SONESSE 50 10/28	230	50	10	28	180	0,78	750
	SONESSE 50 15/17	230	50	15	17	153	0,67	750
SOMFY® RTS	ALTUS 50 6/32	230	50	6	32	90	0,39	790
	ALTUS 50 15/17	230	50	15	17	140	0,61	790
SOMFY® RTS QUIET ⁽¹⁾	SONESSE 50 6/28	230	50	6	28	146	0,63	930
	SONESSE 50 10/28	230	50	10	28	180	0,78	930
	SONESSE 50 15/17	230	50	15	17	153	0,67	930
SOMFY® IO	SUNEA SCREEN 50 6/32	230	50	6	32	120	0,52	790
	SUNEA SCREEN 50 15/32	230	50	15	32	240	1,04	810

⁽¹⁾ (1) Motor only compatible for indoor installation. / (2) Motor with electronic limit switch. / To guarantee proper functioning, Bandalux will provide the right motor model for the shade size.

BANDALUX