



Fit Box

Box roller shade with a cassette and side channels that fits perfectly into windows and glass doors thanks to its installation versatility: it is available in front and inside mount installation.

COLORS:

- White (RAL 9016)
- Anodized aluminum
- Black (RAL 9011)
- Anthracite (RAL 7016)
- Brown (RAL 8017)

**Minimum sizes
(width x height)**

200 x 200 mm

**Maximum sizes
(width x height)**

1600 x 2500 mm

Operating systems

Handle
Chain
Motor

Installation

Front installation
(adhesive on the frame)
Inside mount installation


Options

Personalization
Safekids

System benefits

A multifunctional design

A highly versatile shade that can be placed on the front or inside the window and glass-door frames.



Perfectly integrated into the frame of windows and glass-doors. Semi-opaque side guides for an important light blocking when configured with blackout fabrics. To obtain more concealment, it is necessary to increase the gap between the shade and the glass.

Aluminum bottom bar available for rechargeable battery motor, chain and handle operating system. With handle operating system, the bottom bar allows to releases the spring.

Easy to install

It can be installed in four simple steps: measurement, clean the application area, place the self-supporting adhesive side channels and covers and, finally, clip on the box, which is delivered fully assembled.



No holes, no drilling, no screws.



Ultra-resistant adhesive with the 3M warranty.¹



Front installation is required for windows and doors with internal moldings.

① * It's recommended to follow the manufacturer's assembly and cleaning instructions.

Easy cleaning, maintenance and access to the motor

The box can be removed easily to facilitate the shade and window maintenance and cleaning tasks. A unique innovation patented by Bandalux worldwide.



Tabs on both sides of the drawer to extract the box.



No side channels deterioration as they don't need to be uninstalled or removed.



Easy access to the rechargeable motor from the cover that hides the connection at the end of the box.



Avoids damage or stains on the window when fixing the side channels to the frame.

Safety is our priority

Bandalux offers the perfect safety system in both motor and handle operating systems.



The rechargeable battery motor and handle operation systems are the perfect choice for places with children, as they don't use chains.

The chain operation system is equipped with a child safety system to prevent entanglement.

Bandalux quality

A unique user experience

All Bandalux products offer to the customer a perfect sensory and aesthetic user experience.



Smooth and quiet motion.



This system prevent chain contact and friction with the aluminum profiles.



No visible edges on the aluminum profiles.

Customize every detail


Bandalux offers several options to allow the customers to personalize and configure their blinds as they want until the very last detail.



Wide range of fabric for all applications.



Digital Printing. Print high resolution photos on the shade.




Cassette, side channels and bottom bar available in 5 colors: white, black, brown, anodized aluminum and anthracite. Other RAL options are available.

System benefits

LYNX, smart blinds

The app that allows you to control all Bandalux window coverings solutions, wherever you are.



Available for
Android and iOS.
Compatible with:



amazon alexa



Google Home

Contactless comfort

Manage your blinds from your Smartphone or via voice control.

Atmospheres personalization

Program and automate as many scenes as you want and confirm the position of your blinds at any time.

Peace of mind

Enable presence simulation scenes when you are away from home.

Efficiency and savings

Take advantage of sunlight cycles, react to the climatic conditions and, as a consequence, save on your electricity bill.

Connected environment


In addition to blinds, LYNX allows you to connect other elements such as music, lamps, fans...

Air purifying shades

As a result of Bandalux' ongoing technological innovation and its commitment to sustainability, it has launched a new shade able to purify the air in any room.

Application of a nanocoating on the technical fabric


The shade is treated as follows:



A mixture of oxide minerals is applied to the shade's fabric.



This mixture is naturally activated by sunlight or artificial lighting.



When it is activated, any contaminant particles in the air are removed (viruses, bacteria, fungi, contamination, and volatile organic compounds).



Great versatility

- Applicable to all Roller Shades systems, Box range, Fit Box and Skylight.
- Available in the Polyscreen® 550 and Mega BO fabrics, in a range of colors.

POLYSCREEN® 550 AIRPURE®



Ash

Pearl

White

White Linen

White Pearl

MEGA BO AIRPURE®



Alabaster

Black

Dark Grey

White

Fit Box

OPTIONS

BASE PRICE LIST (INCLUDED IN THE PRICE)

CHAIN-OPERATED FIT BOX CHANNELS CHILD SAFETY PROFILE WITH 3M
AND BOTTOM BAR CHAIN RETAINER ADHESIVE TAPE



Optional: Safekids security device.

PROFILE COLORS White RAL 9016 Anodized aluminum Black RAL 9011 Anthracite RAL 7016 Brown RAL 8017

ⓘ If you do not indicate a different color on the order form or eBa, it will be served in white by default.

COLLECTION AIRPURE®

BANDALUX



airPURE®
BLINDS & SHADES

AIRPURE® SHADES:

- Collection Polyscreen® 550 Airpure® in the following colors: Ash, Pearl, White, White Linen and White Pearl.
- Collection Mega BO Airpure® in the following colors: Alabaster, Black, Dark Grey and White.

OTHER OPTIONS

TRANSPARENT CHAIN



SAFEKIDS
(CHILD SAFETY SYSTEM)



PATENTED
BANDALUX

PERSONALIZATION



OPERATING SYSTEMS

Handle



Motor

MOTOR BATTERY (12V)

BANDALUX RECHARGEABLE BI ø15 0,3/30

ⓘ Charger required

AUTOMATISMS		
SINGLE-CHANNEL REMOTE CONTROL	MULTI-CHANNEL REMOTE CONTROL	OTHER OPTIONS
TRANSMITTER 1 channel Ref. 06701100B	TRANSMITTER 15 channels Ref. 06701110B	AC CHARGER Rechargeable Battery Ref. 06701200

MOTORIZATION

CONFIGURATION OF A SHADE WITH ONE OR SEVERAL COMMAND POINTS



BATTERY MOTOR 15
BANDALUX



SINGLE-
CHANNEL
TRANSMITTER
06701100B
WHITE



CHARGER FOR AC
RECHARGEABLE BATTERY
06701215




CABLE USB TYPE C
06701275



CONFIGURATION OF TWO OR MORE SHADES WITH ONE OR SEVERAL COMMAND POINTS



BATTERY MOTOR 15
BANDALUX



15 CHANNEL
TRANSMITTER
06701110B
WHITE



CHARGER FOR AC
RECHARGEABLE BATTERY
06701215



CABLE USB TYPE C
06701275




OPERATING SYSTEM AND MINIMUM SHADE WIDTH

Operating system	Name of motor	Ø mm	Nm	r.p.m.	Power (W)	Amperes (amp)	Minimum shade width (mm)
HANDLE							580
CHAIN							200 (1)
BANDALUX MOTOR – BATTERY	Rechargeable BI ø15 0,3/30	15	0,3	30	5	0,42	420

(1) (1) Maximum height 1500 mm.

CONTROLS HEIGHT



CHAIN WITH CHILD SAFETY SYSTEM

The **Child Safety/Safekids** piece must be positioned at a minimum height of 1,5m from the floor.

CHAIN WITHOUT CHILD SAFETY SYSTEM

Minimum calculation for hc:
Shade height H x 0,45 + 50 mm


The controls height will always be measured from the uppermost section of the shade (upper end of the bracket) to the lowest end of the chain tensioner.

Example of calculation:


Shade height H	Controls height hc (minimum)
600 mm	320 mm
1200 mm	590 mm
1800 mm	860 mm

CASSETTE SIZE


CASSETTE (SIDE VIEW)



CASSETTE (FRONTAL VIEW)




FIT BOX SIDE CHANNEL




(1) Measurements in mm.

BOTTOM BAR AND RETRACTION HEIGHT


CHAIN / MOTOR




CHAIN/MOTOR RETRACTION HEIGHT



EXTENDED SPRING



HANDLE RETRACTION HEIGHT



(1) Measurements in mm.

(*) (*) The sealing strip is not included for the front installation.

Fit Box

TAKING MEASUREMENTS



ALLOWED
INSTALLATION

Front installation


CHECKING THE MEASUREMENTS

1 The cassette can be installed at any window or glass door height as it does not incorporate adhesive.

Minimum height to ensure that the drawer does not cover the glazed area: **56,5 mm** (the cassette is seen from behind the door)

Minimum height to ensure that the cassette and the bottom bar with chain or motor operating system do not cover the glazed area: **84 mm**

Minimum height to ensure that the cassette and the bottom bar with handle operating system do not cover the glazed area: **103 mm**



2 Minimum space to fix the side guide to the frame: **15 mm** (part of the side guide will overlap on the glass surface)

Minimum space to conceal the side guide in the frame: **27 mm**



3 Minimum space of **30 mm** between the doorknob and the edge of the inner molding.




① Images intended to serve as examples only.

TAKING THE RIGHT MEASUREMENTS

① The Fit Box system can be installed on flat surfaces, glass doors or windows with moldings and crossbars.

To obtain more concealment, it is necessary to increase the gap between the shade and the glass.



① Measurements in mm.

① Minimum space to hide the cassette. ② Optimal space for chain or motorized systems. ③ Optimal space for handle systems. ④ With a margin of 27 mm or wider, the side channel will not be visible from the behind and will not reduce the light path.

ORDER:

Bandalux will supply the shades with the measurements provided by the customer.



ALLOWED
INSTALLATION


Inside mount installation

CHECKING THE MEASUREMENTS

- 1** Take **3 widths** and note the smallest one.
Take **2 heights** and note the smallest one.

- 2** The inside mount installation
requires a minimum **depth of 9 mm**.

TAKING THE RIGHT MEASUREMENTS



Measurements in mm.

ORDER:

When placing your order with Bandalux, it is necessary to indicate the exact measurement of the recess (without deducting anything).

contract.bandalux.com

bandalux.com