

B-BOX® & B-BOX® DUO

Elegance and contemporary design are what define the B-Box® from Bandalux. Made of durable, highly resistant materials with a premium finish that make our B-Box® suitable for indoor or outdoor applications. B-Box® is available in single or dual shade configurations to reduce heat and add beauty.



AVAILABLE COMPONENT COLORS



Anodized



Black



Dark Brown



White

OPERATING SYSTEM



Chain



Motor

 Only indoor installation.

MAXIMUM WIDTH

212" x 64"

MAXIMUM HEIGHT


76" x 275"

 Check 'Fabric Limits' in ProArea.

BOX SYSTEMS - B-BOX®

Strong and simple mounting

Bandalux has developed stronger idle ends to deliver benchmark endurance and reliability. It contains a solid system with high quality bearings that provides a perfect, smooth and silent (motion) rotation. It can be easily set up by a simple one hand move thanks to its internal compression spring.



Smoothen and silent motorization

All Bandalux motorization products include a brand new, hybrid technology driving wheel specifically designed by us to minimize noise and vibration.



Two shades, one operating system

Bandalux's new transmission delivers enhanced smoothness enabling two rolling tubes to operate with just one operating system. New bearings have been added to the mechanism to provide silent and perfect, concentric movement.

Height deviations may appear. These deviations are established according to EN13120 standard: $\pm 3\%$ for each fabric. Maximum height deviation between two fabrics being $\pm 6\%$.



Easy installation

Both for ceiling and wall, the systems have been engineered to ensure a secure yet simple installation for indoor and outdoor applications. Both the Click-On brackets and the reinforced outdoor Slide-On brackets can be used for mounting on conditions that require either ceiling or front-wall installation. All while maintaining its aesthetic design.



Simple maintenance

The roller shade is protected from the dirt thanks to the box system design. The fabric roll can be accessed without the need for complex tools, making maintenance easy and avoiding the need to disassemble the device.

A system that combines aesthetics, durability, and efficiency for both indoor and outdoor installations.



Perimeter closure with a sill channel

For fully concealed systems, a profile is integrated to the base where the fabric lays to ensure a perimeter closure of the entire system in which the shade is integrated, reducing light leakage.



Optimal guide systems

Bandalux offers a wide range of guiding options in both indoor and outdoor solutions that ease fabric movement, responding to Bandalux priority of light control between channel and fabrics.


Cable lateral guides

Holds the fabric and allows its outdoor installation.



Aluminum side channels

Engineered to work with semi-opaque systems. The external channel adapts to uneven wall surfaces and the interior channel adapts to the fabric.



BOX SYSTEMS - B-BOX®

High energy-saving when installed outside

B-Box® provides provable energy savings on air conditioning when configured with efficient fabrics that offer thermal properties and a high degree of reflection.



Smooth and silent

The chain runs on a support equipped with radiated funnels that provide a smooth drive and reduce the noise when operated.



Safety protection for children

In compliance with the updated child safety standard (ANSI/WCMA A100.1-2022), Bandalux supplies an improved Chain/Cord Tension Device by default.

This device is designed to eliminate free hanging cords and connectors in order to be fully tensioned and fixed to the wall with the aim of preventing children from getting entangled in it.

Features of the new Child Safety Device:

- Easy device assembly.
- Quick installation.
- Smooth and reliable performance.




Maximum comfort, smooth operation

Bandalux has developed a brand new system to reduce the effort and weight sensation when operating your shades.

Redux® system

The system reduces up to 35% of its weight in any size (it does not include a limit stop (endless chain)).



Spring assist

Minimize weight sensation in shades larger than 6 sq yds (it includes a limit stop (endless chain)).



142" x 157" shade example:
Effort without spring assist = 10.6 lbs
Effort with spring assist = 4.9 lbs

B-Box® Duo: two solutions in one system

Our B-Box® Duo is the perfect solution when you want both complete blackout and light filtering or decorative options. Using our side channels prevents virtually any light leakage. Perfect for bedrooms when you want blackout sometimes, privacy with sunlight others.



Even the smallest details are considered

Component color combination

Bandalux combines its style with all the system components to deliver best in class products.



Bottom hembar wide assortment

Bottom hembars become a differential element:

Mini Plain (included by default)



Slim 35




Euroslim



Mini Plain fabric wrap



Round fabric wrap ($\phi\frac{3}{4}$ ", $\phi\frac{13}{16}$ ")




BOX SYSTEMS - B-BOX® 2.5

OPTIONS

Standard configuration

Colors



By default, Bandalux will provide the B-Box® 2.5 in white unless a different color is indicated on the order form or eBa.

Chain operated



Mini Plain bottom hembar



Chain Tension Device



Optional configuration

BOTTOM HEMBARS

Slim 35



Euroslim



Mini Plain fabric wrap



Ø 3/4" and Ø 1 3/16" Round fabric wrap



Only available for free drop.

Optional configuration




Metallic chain



Profile special color

Customized hardware colors available upon request. RAL number must be indicated.

Aluminum side channels (indoor installation)




R2 Telescopic front R2 Telescopic lateral



Only compatible with Mini Plain and Euroslim bottom hembars. / Maximum height: 137".




Sill bottom for R2 Telescopic channel




Cable guides (indoor/outdoor installation)

Wall
fixing



Floor
fixing



Ø1/8" Stainless cable guide

Ceiling/Floor

TS

Ceiling/Wall

TP

Wall/Floor

PS

Wall/Wall

PP

Only compatible with Ø3/4" Round fabric wrap, Ø13/16" Round fabric wrap, and Slim 35 bottom hembars.

Operating system options

MOTOR ⁽¹⁾			ACCESSORIES					
RADIO	Somfy® RTS ⁽⁵⁾	SONESSE 40 4/36 120Vac	Single channel remote control	Multi channel remote control	Wirefree wall switch	Charger for battery motors	Battery motor cable extender	Wifi RTS interface
LOW VOLTAGE RADIO	Somfy® RTS ⁽⁵⁾	QUIET 40 6/33 120Vac	Situo 1 Ref. 06700604C	Situo 5 Ref. 06700606C	RTS 5 CH Ref. 06705020	--	--	MyLink Ref. 06700949
	Vertilux	ULTRA QUIET 50 6/28 120Vac	1 CH Ref. 18510110B	6 CH Ref. 18510120B	6 CH Ref. 18500150	--	--	VTi Smart Hub Ref. 12132001
LOW VOLTAGE RECHARGEABLE BATTERY ⁽²⁾	Bandalux ⁽⁴⁾	RADIO BI 25 1.1/40 ⁽³⁾ Built-in transformer 24Vdc	1 CH Ref. 06701100B	15 CH Ref. 06701110B	15 CH Ref. 06701180B	--	--	--
		RADIO BI 28 2/28 Built-in transformer 24Vdc						
Somfy® RTS ⁽⁵⁾	Somfy® RTS ⁽⁵⁾	R28 ⁽³⁾ Battery pack 12Vdc	Situo 1 Ref. 06700604C	Situo 5 Ref. 06700606C	RTS 5 CH Ref. 06705020	--	--	MyLink Ref. 06700949
		SONESSE 30 2/28 ⁽⁵⁾ Transformer included 24Vdc						
Somfy® RTS ⁽⁵⁾	Somfy® RTS ⁽⁵⁾	SONESSE 30 RECHARGEABLE 2/28 WF 12Vdc	Situo 1 Ref. 06700604C	Situo 5 Ref. 06700606C	RTS 5 CH Ref. 06705020	Charger Ref. 05499582	Cable ext. 96" Ref. 05499583	MyLink Ref. 06700949
		SONESSE 40 RECHARGEABLE 3/28 WF 12Vdc						
		RECHARGEABLE R28 WF ⁽³⁾ 12Vdc						
Rollease Automate ⁽⁵⁾	Rollease Automate ⁽⁵⁾	LI-ION 25 1.1 ⁽³⁾ 12Vdc	1 CH Ref. 05499930	15 CH Ref. 05499935	5 CH Ref. 05499990	Charger Ref. 05499920	Cable ext. 96" Ref. 05499921	Pulse Hub Ref. 05499971
		LI-ION 28 2.0 12Vdc						
		LI-ION 40 3.0 Not quiet 12Vdc						
Bandalux ⁽⁴⁾	Bandalux ⁽⁴⁾	RECHARGEABLE BI 25 11/40 ⁽³⁾ 12Vdc	1 CH Ref. 06701100B	15 CH Ref. 06701110B	15 CH Ref. 06701180B	Charger Ref. 06701210	Cable ext. 8FT Ref. 06701250	--
		RECHARGEABLE BI 28 2/28 12Vdc						
		RECHARGEABLE BI 40 3/28 12Vdc						
Vertilux	Vertilux	RECHARGEABLE 38 1.2/30 ⁽³⁾ 7.4Vdc	1 CH Ref. 18510110B	6 CH Ref. 18510120B	6 CH Ref. 18500150	Charger Ref. 05499411	--	VTi Smart Hub Ref. 12132001
		RECHARGEABLE 38 1.8/30 7.4Vdc						
		RECHARGEABLE 40 6/18 12Vdc						

(1) To guarantee a proper functionality Bandalux will provide the appropriate motor model according to the shade size. / **(2)** Price for RECHARGEABLE battery motors includes 1 charger and 1 cable extender per order. / **(3)** Only for width less than 31". / **(4)** Please refer to your sales representative for Bandalux motor delivery deadlines. / **(5)** Motor only compatible for indoor installation.

BOX SYSTEMS - B-BOX® 2.5

OPTIONS

Additional brackets



Wall/Ceiling
indoor
installation



Ceiling
reinforced
bracket



Wall
reinforced
bracket

⚠ Not compatible with front-installed aluminum side channels.

Two shades



Two shades with
2 operating systems



Two shades with 1 operating
system (transmission)

⚠ The maximum width for each shade will be the same as the one established in FABRIC LIMITS book (maximum combined width: 236").


⚠ Chain-operated: the maximum width for both shades cannot exceed the maximum width of a single shade according to FABRIC LIMITS book (maximum combined width: 236").

Motor-operated: the maximum width for the controls side shade cannot exceed the maximum width of a single motor-operated shade according to FABRIC LIMITS book; the maximum width for opposite side shade cannot exceed the maximum width of a single chain-operated shade according to FABRIC LIMITS book; (maximum combined width: 236").

Other options



Fabric customization
Check 'Digital Printing' rate




Opposite rolling
direction installation

⚠ Not available for chain-operated system.
For more information, please check technical data.

Standard configuration

Colors



By default, Bandalux will provide the B-Box® 3 in white unless a different color is indicated on the order form or eBa.

Chain operated



Mini Plain bottom hembar



Chain Tension Device



Optional configuration

BOTTOM HEMBARS

Slim 35



Euroslim



Mini Plain fabric wrap



Ø 3/4" and Ø 1 3/16" Round fabric wrap



Only available for free drop.

Optional configuration



Metallic chain

Silver White

Profile special color

Customized hardware colors available upon request. RAL number must be indicated.

Reduced effort for chain-operated systems



Redux® system

Bandalux recommends REDUX® SYSTEM:

Chain clutch mechanism that **reduces up to 35% of the shade's weight**.

• Redux® systems do not include a limit stop (endless chain). / The chain route length is three times the shade height.



Spring assist

Recommended for shades larger than 6 sq yds:

142" x 157" shade example:

- Effort without spring assist = 10.6 lbs
- Effort without spring assist = 4.9 lbs

BOX SYSTEMS - B-BOX® 3


OPTIONS

Operating system options

MOTOR ⁽¹⁾		ACCESSORIES					
		Single channel remote control	Multi channel remote control	Wirefree wall switch	Charger for battery motors	Battery motor cable extender	Wifi RTS interface
RADIO	Somfy® RTS	SONESSE 40 4/36 ⁽⁵⁾ 120Vac	Situo 1 Ref. 06700604C	Situo 5 Ref. 06700606C	RTS 5 CH Ref. 06705020	--	--
		SONESSE 50 6/32 ⁽⁵⁾ 120Vac					
		ULTRA QUIET 50 6/24 120Vac					
LOW VOLTAGE RADIO	Vertilux	QUIET 40 6/33 120Vac	1 CH Ref. 18510110B	6 CH Ref. 18510120B	6 CH Ref. 18500150	--	--
		ULTRA QUIET 50 6/28 120Vac					
	Bandalux ⁽⁴⁾⁽⁵⁾	RADIO BI 25 1.1/40 ⁽³⁾ Built-in transformer 24Vdc	1 CH Ref. 06701100B	15 CH Ref. 06701110B	15 CH Ref. 06701180B	--	--
LOW VOLTAGE RECHARGEABLE BATTERY ⁽²⁾	Somfy® RTS ⁽⁵⁾	RADIO BI 28 2/28 Built-in transformer 24Vdc					
		R28 ⁽³⁾ Battery pack 12Vdc	Situo 1 Ref. 06700604C	Situo 5 Ref. 06700606C	RTS 5 CH Ref. 06705020	--	--
		SONESSE 30 2/28 ⁽⁵⁾ Transformer included 24Vdc					
Somfy® RTS ⁽⁵⁾	SOMFY 30 RECHARGEABLE 2/28 WF 12Vdc	Situo 1 Ref. 06700604C	Situo 5 Ref. 06700606C	RTS 5 CH Ref. 06705020	Charger Ref. 05499582	Cable ext. 96" Ref. 05499583	MyLink Ref. 06700949
	SOMFY 40 RECHARGEABLE 3/28 WF 12Vdc						
	RECHARGEABLE R28 WF 12Vdc						
Rolese Automate ⁽⁵⁾	LI-ION 25 1.1 ⁽³⁾ 12Vdc	1 CH Ref. 05499930	15 CH Ref. 05499935	5 CH Ref. 05499990	Charger Ref. 05499920	Cable ext. 96" Ref. 05499921	Pulse Hub Ref. 05499971
	LI-ION 28 2.0 12Vdc						
	LI-ION 40 3.0 Not quiet 12Vdc						
Bandalux ⁽⁴⁾⁽⁵⁾	RECHARGEABLE BI 25 1.1/40 ⁽³⁾ 12Vdc	1 CH Ref. 06701100B	15 CH Ref. 06701110B	15 CH Ref. 06701180B	Charger Ref. 06701210	Cable ext. 8FT Ref. 06701250	--
	RECHARGEABLE BI 28 2/28 12Vdc						
	RECHARGEABLE BI 40 3/28 12Vdc						
	RECHARGEABLE BI 50 3/28 12Vdc						
	RECHARGEABLE BI 50 10/9 12Vdc						
Vertilux ⁽⁵⁾	RECHARGEABLE 38 1,2/30 ⁽³⁾ 7.4Vdc	1 CH Ref. 18510110B	6 CH Ref. 18510120B	6 CH Ref. 18500150	Charger Ref. 05499411	--	VTi Smart Hub Ref. 12132001
	RECHARGEABLE 38 1,8/30 7.4Vdc						
	RECHARGEABLE 40 6/18 12Vdc						

⁽¹⁾ To guarantee a proper functionality Bandalux will provide the appropriate motor model according to the shade size. / ⁽²⁾ Price for RECHARGEABLE battery motors includes 1 charger and 1 cable extender per order. / ⁽³⁾ Only for width less than 31". / ⁽⁴⁾ Please refer to your sales representative for Bandalux motor delivery deadlines. / ⁽⁵⁾ Motor only compatible for indoor installation.

Aluminum side channels (indoor installation)




R2 Telescopic front
R2 Telescopic lateral



Only compatible with Mini Plain and Euroslim bottom hembars. / Maximum height: 137".



Sill bottom for R2 Telescopic channel




R2 double channels Kit




Maximum height: 137".

Cable guides (indoor/outdoor installation)

Wall
fixing



Floor
fixing



Ø3/32" Cable guide (indoor)

Ø1/8" Stainless cable guide* (indoor/outdoor)

*Only compatible with Ø3/4" Round fabric wrap, Ø13/16" Round fabric wrap, and Slim 35 bottom hembars.

Ceiling/Floor
Ceiling/Wall
Wall/Floor
Wall/Wall

TS
TP
PS
PP

Additional brackets



Wall/Ceiling
indoor
installation



Ceiling
reinforced
bracket



Wall
reinforced
bracket

* Not compatible with front-installed aluminum side channels.

Two shades



Two shades with
2 operating systems



Two shades with 1 operating
system (transmission)

* The maximum width for each shade will be the same as the one established in FABRIC LIMITS book (maximum combined width: 236").


* Chain-operated: the maximum width for both shades cannot exceed the maximum width of a single shade according to FABRIC LIMITS book (maximum combined width: 236").
Motor-operated: the maximum width for the controls side shade cannot exceed the maximum width of a single motor-operated shade according to FABRIC LIMITS book; the maximum width for opposite side shade cannot exceed the maximum width of a single chain-operated shade according to FABRIC LIMITS book; (maximum combined width: 236").

Other options



Fabric customization

Check 'Digital Printing' rate



Opposite rolling
direction installation


* Not available for chain-operated system. / For more information, please check technical data.

BOX SYSTEMS - B-BOX® 4

OPTIONS

Standard configuration

Colors



By default, Bandalux will provide the B-Box® 4 in white unless a different color is indicated on the order form or eBa.

Chain operated



Mini Plain bottom hembar



Chain Tension Device



Optional configuration

BOTTOM HEMBARS

Slim 35



Euroslim



Mini Plain fabric wrap



Ø 3/4" and Ø 1 3/16" Round fabric wrap



Only available for free drop.

Optional configuration



Metallic chain



Profile special color

Customized hardware colors available upon request.
RAL number must be indicated.

Reduced effort for chain-operated systems



Redux® system

Bandalux recommends REDUX® SYSTEM:

Chain clutch mechanism that **reduces up to 35% of the shade's weight**.

• Redux® systems do not include a limit stop (endless chain). / The chain route length is three times the shade height.



Spring assist

Recommended for shades larger than 6 sq yds:

142" x 157" shade example:

- Effort without spring assist = 10.6 lbs
- Effort without spring assist = 4.9 lbs


Operating system options

MOTOR

MOTOR ⁽¹⁾		ACCESSORIES					
		Single channel remote control	Multi channel remote control	Wirefree wall switch	Charger for battery motors	Battery motor cable extender	Wifi RTS interface
RADIO	Somfy® RTS	SONESSE 40 4/36 ⁽⁴⁾ 120Vac	Situo 1 Ref. 06700604C	Situo 5 Ref. 06700606C	RTS 5 CH Ref. 06705020	--	MyLink Ref. 06700949
		SONESSE 50 6/32 ⁽⁴⁾ 120Vac					
		SONESSE 50 10/32 ⁽⁴⁾ 120Vac					
		ULTRA QUIET 50 6/24 120Vac					
LOW VOLTAGE RECHARGEABLE BATTERY ⁽²⁾	Vertilux	QUIET 40 6/33 120Vac	1 CH Ref. 18510110B	6 CH Ref. 18510120B	6 CH Ref. 18500150	--	VTi Smart Hub Ref. 12132001
		ULTRA QUIET 50 6/28 120Vac					
	Somfy® RTS	SONESSE 40 RECHARGEABLE 3/28 WF ⁽⁴⁾ 12Vdc	Situo 1 Ref. 06700604C	Situo 5 Ref. 06700606C	RTS 5 CH Ref. 06705020	Charger Ref. 05499582	Cable ext. 96" Ref. 05499583
	Rollelease Automate ⁽⁴⁾	LI-ION 40 3.0 Not quiet 12Vdc	1 CH Ref. 05499930	15 CH Ref. 05499935	5 CH Ref. 05499990	Charger Ref. 05499920	Cable ext. 96" Ref. 05499921
		LI-ION 50 3.0 12Vdc					
		LI-ION 50 10.0 12Vdc					
LOW VOLTAGE RECHARGEABLE BATTERY ⁽²⁾	Bandalux ⁽³⁾⁽⁴⁾	RECHARGEABLE BI 40 3/28 12Vdc	1 CH Ref. 06701100B	15 CH Ref. 06701110B	15 CH Ref. 06701180B	Charger Ref. 06701210	Cable ext. 8FT Ref. 06701250
		RECHARGEABLE BI 50 3/28 12Vdc					
		RECHARGEABLE BI 50 10/9 12Vdc					
	Vertilux ⁽⁴⁾	RECHARGEABLE 40 6/18 12Vdc	1 CH Ref. 18510110B	6 CH Ref. 18510120B	6 CH Ref. 18500150	Charger Ref. 05499412	--
	VTi Smart Hub Ref. 12132001						

(1) To guarantee a proper functionality Bandalux will provide the appropriate motor model according to the shade size. / **(2)** Price for rechargeable battery motors includes 1 charger and 1 cable extender per order. / **(3)** Please refer to your sales representative for Bandalux motor delivery deadlines. / **(4)** Motor only compatible for indoor installation.

Aluminum side channels (indoor installation)




R2 Telescopic front
R2 Telescopic lateral



(1) Only compatible with Mini Plain and Euroslim bottom hembars. / Maximum height: 137".



Sill bottom for
R2 Telescopic
channel



R2 double channels Kit




(1) Special order. Delivery time: 6-8 weeks. / Maximum height: 137".

BOX SYSTEMS - B-BOX® 4


OPTIONS

Cable guides (indoor/outdoor installation)

Wall
fixing



Floor
fixing



Ø³/₃₂" Cable guide (indoor)

Ø¹/₈" Stainless cable guide* (indoor/outdoor)

Ceiling/Floor
Ceiling/Wall
Wall/Floor
Wall/Wall

TS
TP
PS
PP

• *Only compatible with Ø³/₄" Round fabric wrap, Ø¹/₁₆" Round fabric wrap, and Slim 35 bottom hembars.

Additional brackets



Wall/Ceiling
indoor
installation



Ceiling
reinforced
bracket



Wall
reinforced
bracket

• Not compatible with front-installed aluminum side channels.

Two shades



Two shades with
2 operating systems



Two shades with 1 operating
system (transmission)

• The maximum width for each shade will be the same as the one established in FABRIC LIMITS book (maximum combined width: 236").


• Chain-operated: the maximum width for both shades cannot exceed the maximum width of a single shade according to FABRIC LIMITS book (maximum combined width: 236").

Motor-operated: the maximum width for the controls side shade cannot exceed the maximum width of a single motor-operated shade according to FABRIC LIMITS book; the maximum width for opposite side shade cannot exceed the maximum width of a single chain-operated shade according to FABRIC LIMITS book; (maximum combined width: 236").

Other options



Fabric customization




Opposite rolling
direction installation

• Not available for chain-operated system. / For more information, please check technical data.

Standard configuration

Colors



By default, Bandalux will provide the B-Box® 5 in white unless a different color is indicated on the order form or eBa.

Chain operated



Mini Plain bottom hembar



Chain Tension Device



Optional configuration

BOTTOM HEMBARS

Slim 35



Euroslim




Mini Plain fabric wrap



Only available for free drop.

Ø³/₄" and Ø¹₁₆" Round fabric wrap



Optional configuration



Metallic chain



Profile special color

Customized hardware colors available upon request.
RAL number must be indicated.

Reduced effort for chain-operated systems




Redux® system

Bandalux recommends REDUX® SYSTEM:

Chain clutch mechanism that **reduces up to 35% of the shade's weight**.

• Redux® systems do not include a limit stop (endless chain). / The chain route length is three times the shade height.



Spring assist

Recommended for shades larger than 6 sq yds:

142" x 157" shade example:

- Effort without spring assist = 10.6 lbs
- Effort without spring assist = 4.9 lbs

BOX SYSTEMS - B-BOX® 5

OPTIONS


Operating system options

MOTOR

MOTOR ⁽¹⁾		ACCESSORIES					
		Single channel remote control	Multi channel remote control	Wirefree wall switch	Charger for battery motors	Battery motor cable extender	Wifi RTS interface
RADIO	Somfy® RTS	SONESSE 50 6/32 ⁽⁴⁾ 120Vac	Situo 1 Ref. 06700604C	Situo 5 Ref. 06700606C	RTS 5 CH Ref. 06705020	--	MyLink Ref. 06700949
		SONESSE 50 10/32 ⁽⁴⁾ 120Vac					
		ULTRA QUIET 50 6/24 120Vac					
LOW VOLTAGE RECHARGEABLE BATTERY ⁽²⁾	Rollesee Automate ⁽⁴⁾	LI-ION 50 3.0 12Vdc	1 CH Ref. 05499930	15 CH Ref. 05499935	5 CH Ref. 05499990	Charger Ref. 05499920	Cable ext. 96" Ref. 05499921
		LI-ION 50 10.0 12Vdc					
	Bandalux ⁽³⁾⁽⁴⁾	RECHARGEABLE BI 50 3/28 12Vdc	1 CH Ref. 06701100B	15 CH Ref. 06701110B	15 CH Ref. 06701180B	Charger Ref. 06701210	Cable ext. 8FT Ref. 06701250
		RECHARGEABLE BI 50 10/9 12Vdc					

(1) To guarantee a proper functionality Bandalux will provide the appropriate motor model according to the shade size. / **(2)** Price for rechargeable battery motors includes 1 charger and 1 cable extender per order. / **(3)** Please refer to your sales representative for Bandalux motor delivery deadlines. / **(4)** Motor only compatible for indoor installation.

Aluminum side channels (indoor installation)




R2 Telescopic front
R2 Telescopic lateral



(1) Only compatible with Mini Plain and Euroslim bottom hembars. / Maximum height: 137".



Sill bottom for
R2 Telescopic
channel



R2 double channels Kit



(1) Special order. Delivery time: 6-8 weeks. / Maximum height: 137".

Cable guides (indoor/outdoor installation)

Wall
fixing



Floor
fixing



Ø3/16" Stainless Cable guide

Ceiling/Floor	TS
Ceiling/Wall	TP
Wall/Floor	PS
Wall/Wall	PP

(1) Only compatible with Ø13/16" Round fabric wrap and Slim 35 bottom hembars.

BOX SYSTEMS - B-BOX® 5

OPTIONS

Additional brackets



Ceiling reinforced bracket

⚠ Cotter included.



Wall reinforced bracket

⚠ Not compatible with front-installed aluminum side channels. / Cotter included.

Two shades



Two shades with 2 operating systems



Two shades with 1 operating system (transmission)

⚠ The maximum width for each shade will be the same as the one established in FABRIC LIMITS book (maximum combined width: 236").


⚠ Chain-operated: the maximum width for both shades cannot exceed the maximum width of a single shade according to FABRIC LIMITS book (maximum combined width: 236").

Motor: the maximum width for the controls side shade cannot exceed the maximum width of a single motor-operated shade according to FABRIC LIMITS book; the maximum width for opposite side shade cannot exceed the maximum width of a single chain-operated shade according to FABRIC LIMITS book; (maximum combined width: 236").

Other options



Fabric customization



Opposite rolling direction installation


⚠ Only available with aluminum side channels. / Not available for chain-operated system. / For more information, please check technical data.

BOX SYSTEMS - B-BOX® DUO

OPTIONS

Standard configuration

Colors



By default, Bandalux will provide the B-Box® Duo in white unless a different color is indicated on the order form or eBa.

Metallic chain operated



Spring assist



Mini Plain bottom hembar



Chain Tension Device



Only included for shades over 59" wide.




Optional configuration

Plastic chain



BOTTOM HEMBARS

Slim 35



Euroslim



Mini Plain fabric wrap



Ø 3/4" and Ø 1 3/16" Round fabric wrap



Optional configuration

Profile special color

Customized hardware colors available upon request.
RAL number must be indicated.

Reduced effort for chain-operated systems



Redux® system

Bandalux recommends REDUX® SYSTEM:

Chain clutch mechanism that **reduces up to 35% of the shade's weight**.

Redux® systems do not include a limit stop (endless chain). / The chain route length is three times the shade height.



Spring assist

Recommended for shades larger than 6 sq yds:

142" x 157" shade example:

- Effort without spring assist = 10.6 lbs
- Effort without spring assist = 4.9 lbs

BOX SYSTEMS - B-BOX® DUO

OPTIONS

Operating system options

❶ To estimate the full B-Box® Duo shade price you will need to add the two corresponding base price for each one of the selected fabrics. If you desire a motor-operated system, add the corresponding price. Both operating systems must always be on the same side.



Chain
Chain

⚠ Metallic chain served by default.



Motor
Motor




Chain (front shade)
Motor (rear shade)

MOTOR ⁽¹⁾		ACCESSORIES					
		Single channel remote control	Multi channel remote control	Wirefree wall switch	Charger for battery motors	Battery motor cable extender	Wifi RTS interface
RADIO	Somfy® RTS	SONESSE 40 4/32 ⁽⁴⁾ 120Vac	Situo 1 Ref. 06700604C	Situo 5 Ref. 06700606C	RTS 5 CH Ref. 06705020	--	MyLink Ref. 06700949
		SONESSE 50 6/32 ⁽⁴⁾ 120Vac					
		SONESSE 50 10/32 ⁽⁴⁾ 120Vac					
		ULTRA QUIET 50 6/24 120Vac					
LOW VOLTAGE RECHARGEABLE BATTERY ⁽²⁾	Vertilux	QUIET 40 6/33 120Vac	1 CH Ref. 18510110B	6 CH Ref. 18510120B	6 CH Ref. 18500150	--	MyLink Ref. 06700949
		ULTRA QUIET 50 6/28 120Vac					
	Somfy® RTS	SONESSE 40 RECHARGEABLE 3/28 WF ⁽⁴⁾ 12Vdc	Situo 1 Ref. 06700604C	Situo 5 Ref. 06700606C	RTS 5 CH Ref. 06705020	Charger Ref. 05499582	Cable ext. 96" Ref. 05499583
	Rollelease Automate	LI-ION 40 3.0 Not quiet 12Vdc	1 CH Ref. 05499930	15 CH Ref. 05499935	5 CH Ref. 05499990	Charger Ref. 05499920	Cable ext. 96" Ref. 05499921
		LI-ION 50 3.0 12Vdc					
Bandalux ⁽³⁾	Bandalux	RECHARGEABLE BI 40 3/28 12Vdc	1 CH Ref. 06701100B	15 CH Ref. 0670110B	15 CH Ref. 06701180B	Charger Ref. 06701210	Cable ext. 8FT Ref. 06701250
		RECHARGEABLE BI 50 3/28 12Vdc					
		RECHARGEABLE BI 50 10/9 12Vdc					
Vertilux	Vertilux	RECHARGEABLE 40 6/18 12Vdc	1 CH Ref. 18510110B	6 CH Ref. 18510120B	6 CH Ref. 18500150	Charger Ref. 05499412	VTi Smart Hub Ref. 12132001

❶ (1) To guarantee a proper functionality Bandalux will provide the appropriate motor model according to the shade size. / (2) Price for rechargeable battery motors includes 1 charger and 1 cable extender per order. / (3) Please refer to your sales representative for Bandalux motor delivery deadlines. / (4) Motor only compatible for indoor installation.

Aluminum side channels (indoor installation)




R2 Telescopic front
R2 Telescopic lateral



❶ Only compatible with Mini Plain and Euroslim bottom hembars. / Maximum height: 137".



Sill bottom for R2 Telescopic channel



R2 double channels Kit



❶ Special order. Delivery time: 6-8 weeks. / Maximum height: 137".

BOX SYSTEMS - B-BOX® DUO

OPTIONS

Additional brackets



Ceiling reinforced bracket

⚠ Cotter included.



Wall reinforced bracket

⚠ Not compatible with front-installed aluminum side channels. / Cotter included.

Two shades



Two shades with 4 operating systems

⚠ The maximum width for each shade will be the same as the one established in FABRIC LIMITS book (maximum combined width: 236").




Two shades with 2 operating systems (transmission)

⚠ Chain-operated: the maximum width for both shades cannot exceed the maximum width of a single shade according to FABRIC LIMITS book (maximum combined width: 236").

Motor-operated: the maximum width for the controls side shade cannot exceed the maximum width of a single motor-operated shade according to FABRIC LIMITS book; the maximum width for opposite side shade cannot exceed the maximum width of a single chain-operated shade according to FABRIC LIMITS book; (maximum combined width: 236").

Other options



Fabric customization

Operating systems and minimum shade width

OPERATING SYSTEM	MOTOR NAME	Sound Level (dBA)	Ø (mm)	Nm	r.p.m.	IP	Requires charger/transformer	Motor Vdc/Vac	Minimum shade width				
									B-BOX® 2.5	B-BOX® 3	B-BOX® 4	B-BOX® 5	B-BOX® DUO
CHAIN	--	--	--	--	--	--	--	--	8"	8"	8"	8"	8"
SOMFY®	R28	48-56	25	1.1	28	20	No	12 Vdc	19"	19"	--	--	--
	RECHARGEABLE R28 WF	N/I/A	25	1.1	28	20	Yes	12 Vdc	28"	28"	--	--	--
	SONESSE 30 2/28 ⁽⁴⁾	44	30	2	6/28	30	No	24 Vdc	21"	21"	--	--	--
	SONESSE 30 RECHARGEABLE 2/28 WF ⁽⁴⁾	44	30	2	10/28	20	Yes	12 Vdc	28"	28"	--	--	--
	SONESSE 40 4/36 ⁽⁴⁾	42	40	4	36	44	No	120 Vac	25"	25"	25"	--	25"
	SONESSE 40 RECHARGEABLE 3/28 WF ⁽⁴⁾	44	40	3	10/28	30	Yes	12 Vdc	30"	30"	30"	--	30"
	SONESSE 50 6/32 ⁽⁴⁾	≤44	50	6	32	31	No	120 Vac	--	31"	31"	31"	31"
	SONESSE 50 10/32 ⁽⁴⁾	≤45	50	10	32	44	No	120 Vac	--	31"	31"	31"	31"
ROLLESE AUTOMATE	ULTRA QUIET 50 6/24	≤38	50	6	24	31	No	120 Vac	--	37"	37"	37"	37"
	LI-ION 25 1.1	46	25	1.1	40/30/20	44	Yes	12 Vdc	25"	25"	--	--	--
	LI-ION 28 2.0	44	30	2	28/24/20	44	Yes	12 Vdc	30"	30"	--	--	--
	LI-ION 40 3.0	53	35	3	28/24/20	44	Yes	12 Vdc	38"	38"	38"	--	38"
	LI-ION 50 3.0	40	45	3	28/24/20	44	Yes	12 Vdc	--	--	37"	37"	37"
BANDALUX	LI-ION 50 10.0	42	45	10	9/8/6	44	Yes	12 Vdc	--	--	37"	37"	--
	RADIO BI 25 1.1/40	46	25	1.1	40/30/20	44	No	24 Vdc	24"	24"	--	--	--
	RADIO BI 28 2/28	44	28	2	28/24/20	44	No	24 Vdc	32"	32"	--	--	--
	RECHARGEABLE BI 25 1.1/40	46	25	1.1	40/30/20	44	Yes	12 Vdc	27"	27"	--	--	--
	RECHARGEABLE BI 28 2/28	44	28	2	28/24/20	44	Yes	12 Vdc	32"	32"	--	--	--
	RECHARGEABLE BI 40 3/28	53	40	3	28/24/20	44	Yes	12 Vdc	32"	32"	32"	--	32"
	RECHARGEABLE BI 50 3/28	40	50	3	28/24/20	44	Yes	12 Vdc	--	36"	36"	36"	36"
VERTILUX	RECHARGEABLE BI 50 10/9	42	50	10	9/8/6	44	Yes	12 Vdc	--	36"	36"	36"	36"
	RECHARGEABLE 38 1.2/30	N/I/A	38	1.2	30	N/I/A	Yes	7.4 Vdc	22"	22"	--	--	--
	RECHARGEABLE 38 1.8/30	N/I/A	38	1.8	30	N/I/A	Yes	7.4 Vdc	27"	27"	--	--	--
	RECHARGEABLE 40 6/18	N/I/A	35	6	18	N/I/A	Yes	12 Vdc	35"	35"	35"	--	35"
	QUIET 40 6/33	N/I/A	40	6	33	44	No	120 Vac	29"	29"	--	--	29"
	ULTRA QUIET 50 6/28	N/I/A	50	6	28	N/I/A	No	120 Vac	32"	32"	32"	--	32"

⁽¹⁾ For measurements 7 7/8"-15 3/4" wide, maximum height 59 1/16" without guiding. Side guides needed for larger heights. / To guarantee proper functioning, Bandalux will provide the appropriate motor model according to the shade size. / N/I/A: No info available.


⁽⁴⁾ Motor only compatible for indoor installation.

BOX SYSTEMS - B-BOX®

TECHNICAL DATA

Controls height

CHAIN



Minimum calculation for hc :
 $H \times 0.90$

Estimate example

Shade height H	Controls height hc
40"	36"
80"	72"
160"	144"

! The controls height will always be measured from the highest part of the shade (bracket upper part) to the lowest part of the operating system.


Side guide sizes

CABLE GUIDE


$\varnothing 3/32"$ Cable guide (indoor installation)

$\varnothing 1/8"$ Stainless cable guide (indoor/outdoor)

Wall
fixing



Floor
fixing



$\varnothing 3/16"$ Stainless cable guide (indoor/outdoor)

Wall
fixing




Floor
fixing




ALUMINUM SIDE CHANNEL (indoor installation)


R2 Telescopic front



R2 Telescopic lateral




R2 double channels Kit



SILL BOTTOM FOR R2 TELESCOPIC CHANNEL

For B-Box® 2.5/3/4/6/Duo



Box system sizes









NORMAL ROLLING DIRECTION								OPPOSITE ROLLING DIRECTION						
Self-supporting		Wall / Ceiling indoor bracket		Wall reinforced bracket		Ceiling reinforced bracket		Wall reinforced bracket			Ceiling reinforced bracket			
A	B	A	B	A	B	A	B	A	B	C*	A	B	C*	
B-BOX® 2.5	2 ^{11/16} "	2 ^{3/4} "	3 ^{1/8} "	2 ^{7/8} "	3"	2 ^{7/8} "	2 ^{11/16} "	2 ^{7/8} "	3"	3 ^{1/8} "	2 ^{5/8} "	2 ^{11/16} "	3 ^{1/8} "	1 ^{5/16} "
B-BOX® 3	3 ^{7/16} "	3 ^{9/16} "	3 ^{13/16} "	3 ^{5/8} "	3 ^{3/4} "	3 ^{5/8} "	3 ^{7/16} "	3 ^{5/8} "	3 ^{3/4} "	4"	2 ^{5/16} "	3 ^{7/16} "	3 ^{15/16} "	1 ^{15/16} "
B-BOX® 4	4"	4 ^{1/8} "	4 ^{3/8} "	4 ^{1/4} "	4 ^{5/16} "	4 ^{1/4} "	4"	4 ^{1/4} "	4 ^{5/16} "	4 ^{9/16} "	2 ^{7/8} "	4"	4 ^{1/2} "	2 ^{9/16} "
B-BOX® 5	5 ^{3/8} "	5 ^{3/8} "	--	--	5 ^{13/16} "	5 ^{13/16} "	5 ^{3/8} "	5 ^{13/16} "	--	--	--	--	--	--
B-BOX® DUO	5 ^{3/8} "	5 ^{3/8} "	--	--	5 ^{13/16} "	5 ^{13/16} "	5 ^{3/8} "	5 ^{13/16} "	--	--	--	--	--	--

⚠ Opposite rolling direction: NON registerable box system. Not available for chain-operated system. *Worst case scenario (ø13/16" Round fabric wrap bottom hembar).

BOX SYSTEMS - B-BOX®



TECHNICAL DATA

Bottom hembars and retraction heights

	HIDDEN BOTTOM HEMBARS			VISIBLE BOTTOM HEMBARS			
B-BOX® 2.5-5							
B-BOX® DUO							
	A	A	A	A	A	A	
B-BOX® 2.5 ⁽¹⁾	3 11/16"	4 1/16"	4 7/16"	4 7/16"	4 1/4"	4 1/4"	
B-BOX® 3 ⁽¹⁾	4 7/16"	4 13/16"	5 3/16"	5 3/16"	5 1/16"	5 1/16"	
B-BOX® 4 ⁽¹⁾	5"	5 7/16"	5 7/8"	5 7/8"	5 5/8"	5 5/8"	
B-BOX® 5 ⁽¹⁾	6 5/8"	7"	7 3/8"	7 3/8"	7 3/16"	7 3/16"	
B-BOX® DUO ⁽²⁾	6 3/16"	6 5/8"	6 15/16"	6 15/16"	6 13/16"	6 13/16"	
WITHOUT SIDE GUIDES	✓	✓	✓	✗	✓	✓	
WITH CABLE GUIDE	✓	✓	✗	✗	✓	✗	
WITH R2 TELESCOPIC CHANNEL ⁽³⁾	✗	✗	✗	✓	✗	✗	


⁽¹⁾(1) Data for ceiling reinforced bracket. / (2) Data for self-supporting installation. Add 3/8" for ceiling or wall bracket. / (3) In B-Box® Duo system, R2 Telescopic channel only available for rear shade.

Space between bracket and fabric (GAP)

One shade with
1 operating systemTwo shades with
1 operating systemTwo shades with
2 operating systems

		without side guides				with cable guides	
		w1	w2	w3	w4	w1	w2
B-BOX® 2	CHAIN	7/8"	11/16"	11/8"	19/16"	--	--
	12Vdc MOTOR	7/8"	3/4"	11/8"	19/16"	--	--
	24Vdc MOTOR	7/8"	3/4"	11/8"	19/16"	--	--
B-BOX® 2.5	CHAIN	7/8"	13/16"	13/16"	15/16"	7/8"	7/8"
	12Vdc MOTOR	7/8"	3/4"	13/16"	15/16"	7/8"	7/8"
	24Vdc MOTOR	7/8"	3/4"	13/16"	15/16"	7/8"	7/8"
	120Vac MOTOR	7/8"	15/16"	13/16"	15/16"	7/8"	1"
B-BOX® 3	CHAIN	7/8"	13/16"	13/16"	15/16"	7/8"	7/8"
	12Vdc MOTOR	7/8"	3/4"	13/16"	15/16"	7/8"	7/8"
	24Vdc MOTOR	7/8"	3/4"	13/16"	15/16"	7/8"	7/8"
	120Vac MOTOR	7/8"	15/16"	13/16"	15/16"	7/8"	1"
B-BOX® 4	CHAIN	7/8"	13/16"	13/16"	15/16"	7/8"	7/8"
	12Vdc MOTOR	7/8"	3/4"	13/16"	15/16"	7/8"	7/8"
	120Vac MOTOR	7/8"	15/16"	13/16"	15/16"	7/8"	1"
B-Box® 5	CHAIN	7/8"	13/16"	13/16"	15/16"	7/8"	7/8"
	12Vdc MOTOR	7/8"	3/4"	13/16"	15/16"	7/8"	7/8"
	120Vac MOTOR	7/8"	15/16"	13/16"	15/16"	7/8"	1"
B-BOX® DUO	CHAIN	7/8"	13/16"	13/16"	15/16"	--	--
	12Vdc MOTOR	7/8"	3/4"	13/16"	15/16"	--	--
	120Vac MOTOR	7/8"	15/16"	13/16"	15/16"	--	--

Production tolerance



BANDALUX